

# TECHNICAL DATA SHEET

## V-belt spray

**Art. no. 0893 230**

P. Qty.: 1 / 12

### For extending the service life of V-belts

Chemical basis	Mineral oil
Colour	Light yellow
Density	0.673 g/cm <sup>3</sup>
Smell/fragrance	Characteristic
Boiling point	-44 °C
Ignition temperature	250 °C
Silicone-free	Yes
Acid-free	Yes
AOX-free	Yes
Resin-free	Yes
Contents	400 ml
Container	Can
Shelf life from production	24 Month



## Application area

For V-belts made from leather, rubber, balata, hair etc. Not suitable for use on flat belts. When using V-belt spray, contact with the belt pulleys is increased - separation and friction problems are reduced to a minimum. The efficiency of the V-belt is increased.

## Notice

Only use in well-ventilated areas.

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.