

# TECHNICAL DATA SHEET

## Silicone fluid silicone spray

**Art. no. 0893 221 000**

P. Qty.: 1 / 12

### High-quality, physiologically safe anti-friction and release agent

Contains highly concentrated high-quality silicone oils, colourless, non-staining. Good material compatibility. Moisture repellent, protects e.g. rubber parts against frost. Colourless, non-discolouring, reduces wear, good penetration properties, good protection against oxidation and ageing, good compatibility with materials, eliminates squeaking noises, only to be marked with F+.



Contents	0.4 l
Colour	Colourless
Chemical basis	Physiologically harmless synthetic oil
Density/conditions	0.785 g/cm <sup>3</sup> /Active substance, 20 °C
Min./max. temperature conditions	-50 to 250 °C
Shelf life from production	24 Month

### Application area

As an anti-friction agent and for the lubrication of all moving parts of machines, especially in the field of plastics, in automotive engineering and in the food, pharmaceutical, printing and paper industries. Also as a mould release agent in the plastics processing industry and for surface care and protection. Can be used in areas in which food is processed or stored.

### Application information

Pre-clean the surface to be treated. Spray on evenly from a distance of approx. 20 cm. If the product is used in applications that may involve contact with food: Only the minimum quantity technically necessary may be used. If the product is to be used as an anti-corrosive film, it must be completely removed before the device in question is used again.

### Proof of performance

NSF H1-registered (no.: 135927), meets the requirements of USDA 1998 H1.



# TECHNICAL DATA SHEET

## Notice

### NSF H1

The product may come into contact with foodstuffs for technical reasons.

If used in areas in which food is processed or stored, only the minimum quantity technically required may be used. If the product is to be used as an anti-corrosive film, it must be completely removed before the device in question is used again.

The usage instructions are recommendations based on the tests we have conducted and on our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We ensure the consistent quality of our products. We reserve the right to make technical changes and further develop products.