

TECHNICAL DATA SHEET

Heat-resistant crepe masking tape +120 °C

Art. no. 0992 619

P. Qty.: 16

Crepe adhesive tape for painting work with high temperatures

Backing material	Creped paper, latex impregnated
Adhesive base	Rubber resin adhesive
Colour	Brown (base material)
Width	18 mm
Length	50 m
Thickness of adhesive tape	180 µm
Dynamic peel strength at 25 mm	10.5 N
Elongation at break	10.5 %
Min./max. temperature resistance	-20 to 120 °C
Min./max. processing temperature	15 to 40 °C
Ultraviolet resistance	No
Moisture resistance	Yes
Shelf life from production/conditions	18 Month/at 20°C and 50% humidity



Application area

- Painting work in body area, and painting tasks that require oven drying
- Masking tasks in painting sector
- Securing masking paper
- Labelling cardboard boxes and cans

Notice

To ensure residue-free removal, the tape must be removed immediately after the paint or varnish has dried. The adhesive tape is not UV-resistant and is therefore not suitable for outdoor applications.

TECHNICAL DATA SHEET

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.