

TECHNICAL DATA SHEET

Lock cylinder spray

Art. no. 0893 052

P. Qty.: 1 / 12 / 24

For the care of all types of locks

- Excellent creeping properties ensure very good moisture displacement
- Corrosion protection additives prevent the collection of moisture, thereby preventing freezing in winter
- Provides permanent protection of locking mechanisms
- Sensitive components are not attacked
- Resin, acid and silicone-free

Chemical basis	Mineral oil
Colour	Light brown
Smell/fragrance	Perfumed
Density	0.71 g/cm ³
Silicone-free	Yes
Acid-free	Yes
Resin-free	Yes
Contents	50 ml
Container	Aerosol can in a display box
Shelf life from production	24 Month



Application area

For maintaining all types of locks.

Application information

Insert capillary tube into the lock and spray briefly.

Notice

Do not additionally lubricate with graphite powder

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.