

# TECHNICAL DATA SHEET

## Paint spray, matt

**Art. no. 0893 329 005**

P. Qty.: 1 / 12 / 24

### Durable nitro-alkydale quality at a high technical level

- Fast-drying
- Excellent coverage
- Extremely weather-resistant
- Good coverage properties
- Sprays well
- Closed surface
- Easy to apply
- Good resistance to petrol
- Hard surface, not susceptible to scratching
- High solids content
- Very economical



|   |  |
|---|--|
| Contents  | 400 ml   |
| Colour  | Jet black RAL 9005                               |
| Chemical basis                                    | Nitroalkydale                                    |
| Gloss level                                       | Matt   |
| Max. temperature resistance                       | 80 °C  |
| Density   | 0.75 g/cm <sup>3</sup>                           |
| Dust-drying time                                  | 10 min   |
| Min./max. spraying distance                       | 20-25 cm   |
| Min. spraying distance                            | 20 cm  |
| Max. spraying distance                            | 25 cm  |
| Tack-free after                                   | 20 min   |
| Shelf life from production                        | 36 Month   |
| Min. processing temperature for can               | 20 °C  |
| Conditions to maintain shelf life from production | at 15 °C to 25 °C and max. 60% relative humidity |
| Conditions for drying time                        | at 20 °C   |
| Min. flash-off time                               | 5 min  |
| Design  | Round nozzle                                     |
| Free from heavy metals                            | Yes  |
| CFC (fuel gas) free                               | Yes  |

## Application area

For paint repair work, protection from corrosion and weathering, and for surface finishing. Surfaces: Wood, metal, fabric, stone, ceramics, glass, paintable plastics, concrete, wicker. Wide range of uses: Commercial vehicles, bodywork, radiators, window

# TECHNICAL DATA SHEET

construction, steel construction etc.

## Application information

Before using the spray can, carefully read and pay attention to warning texts! Spray only in dry weather, in wind-protected places and well-ventilated spaces. Temperatures preferably between +10°C and +27°C. Shake the can for at least 2 minutes before use to ensure optimum application. The surface must be clean, dry and free from grease. Remove rust and old paint; sand and prime. Do a test spray and then compare the colour. Spraying distance: approx. 20-25 cm. Cover the surrounding area to prevent the spray mist from depositing. Turn the can upside down after use and spray until the valve is empty.

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.