

TECHNICAL DATA SHEET

Adhesive lubricant HHS® 6000 PLUS

Art. no. 0893 106 202

P. Qty.: 1 / 12

High-performance lubricating oil for extreme speeds

Chemical basis	Synthetic oil
Oil basis	Synthetic
Colour	Yellowish
Smell/fragrance	Odourless
Density	0.834 g/ml
Density conditions	at 20 °C, DIN 51757
Min. temperature conditions	-40 °C
Max. temperature conditions	180 °C
Max. temperature resistance	1000 °C
Min. flashing point of active ingredient	200 °C
Min. flashing point	200 °C
Kinematic oil basis viscosity	31 mm ² /s
Conditions for viscosity of oil basis	at 20 °C
Silicone-free	Yes
Acid-free	Yes
Resin-free	Yes
Resistance against	Aging
Contents	400 ml
Weight of content	333.6 g
Shelf life from production	24 Month
Sustainability	Pollutants/Emissions



Application area

For professional use with smallest tolerances, precision parts or even with high temperature loads, such as bearings, chains, joints, springs, sliding rails or Bowden cables.

TECHNICAL DATA SHEET

Proof of Performance



Notice

Physiologically safe lubricant; ideally suited for the food processing industry. NSF H1-registered.

The usage instructions are recommendations based on the tests we have conducted and on our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. If our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee the consistent quality of our products. We reserve the right to make technical changes and further develop products.